

**4b USB 2.4****TECHNICAL FEATURES****USB power supply 5 V, 2.4 A****U SERIES****Application.**

For charging portable devices such as phones, smartphones, tablets, MP3 or MP4 players, speakers, watches, games consoles and powerbanks.

USB A compliance

USB power supply: Test reports issued by IMQ in accordance with EN60950-1:2006 + A11:2009 + A1:2010 + A12:2010 + A2:2013. EMC Directive LV Directive.

Installation

Do not install multiple adjacent power supplies. It is recommended to leave the module adjacent to the USB power supply free.

Main features of USB A power supplies

- USB power supply
- Input voltage: 100...240 V AC (50/60 Hz)
- Output voltage: 5 V, 2.4 A
- Overvoltage category (IEC 60364-4-44) CAT III
- Disconnection device with spacing between the contacts of at least 3 mm

Material specifications

Base: PC / Cover: PC / UV-resistant





Compatible with

Bticino®, Vimar®, Gewiss®.

Compatibility, codes and dimensions

Brand	Model	Colour	Code	A	B	C
Vimar®	Plana™	white	4B.V14.USB.24	44.80	47.40	22.30
	Arkè™	white	4B.V19B.USB.24	44.80	47.40	22.30
		grey	4B.V19.USB.24	44.80	47.40	22.30
		metal	4B.V19M.USB.24	44.80	47.40	22.30
Bticino®	Matix™	white	4B.AM.USB.24	43.35	47.20	23.24
	LivingLight™	white	4B.N.USB.24	43.90	47.20	21.80
		tech	4B.NT.USB.24	43.90	47.20	21.80
		anthracite	4B.L.USB.24	43.90	47.20	21.80
	Axolute™	white	4B.HD.USB.24	45.23	47.20	22.23
		tech	4B.HC.USB.24	45.23	47.20	22.23
		anthracite	4B.HS.USB.24	45.23	47.20	22.23
Gewiss®	Chorus™	white	4B.G10.USB.24	47.20	44.00	22.23
		black	4B.G12.USB.24	47.20	44.00	22.23

Measurements in mm

**Connectors**

2x USB A



Made in P.R.C.

4box.it**4 BOX s.r.l.**

VAT IT07624080961

info@4box.it

phone +39 02 655 603 73

Registered office and operational headquarters

Via Filippo Brunelleschi, 16, 20166 Milan

Tax ID and Business Register No.:07624080961 - Economic and Administrative Index (R.E.A.) 1972154
Chamber of Commerce (C.C.I.A.A.) MI - Share Cap. € 20,000