

**4b USB 2.1**

TECHNICAL FEATURES

USB power supply 5 V, 2.1 A**U SERIES**

Application

For charging portable devices such as phones, smartphones, tablets, MP3 or MP4 players, speakers, watches, games consoles and powerbanks.

USB A compliance

- USB power supply: Test reports issued by IMQ in accordance with EN60950-1:2006 + A11:2009 + A1:2010 + A12:2010 + A2:2013
EMC Directive LV Directive.

Main features of USB A power supplies

- USB power supply
- Input voltage: 100...240 V AC (50/60 Hz)
- Output voltage: 5 V, 2.1 A
- Overvoltage category (EN 62109) Class III
- Disconnection device with spacing between the contacts of at least 3 mm

Material specifications

Base: PC / Cover: PC / UV-resistant

Installation

Do not install multiple adjacent power supplies. It is recommended to leave the module adjacent to the USB power supply free.
Install just one device per flush mount box.





Compatible with

Bticino®, Vimar®, Gewiss®.

Compatibility, codes and dimensions

Brand	Model	Colour	Code	A	B	C
Vimar®	Plana™	white	4B.V14.USB	44.80	47.40	22.30
Bticino®	Matix™	white	4B.AM.USB.24	43.35	47.20	23.24
	LivingLight™	white	4B.N.USB.24	43.90	47.20	21.80
		tech	4B.NT.USB.24	43.90	47.20	21.80
		anthracite	4B.L.USB.24	43.90	47.20	21.80
	Axolute™	white	4B.HD.USB.24	45.23	47.20	22.23
		tech	4B.HC.USB.24	45.23	47.20	22.23
		anthracite	4B.HS.USB.24	45.23	47.20	22.23
Gewiss®	Chorus™	white	4B.G10.USB.24	47.20	44.00	22.23
		black	4B.G12.USB.24	47.20	44.00	22.23

Measurements in mm



Connectors



USB A



Made in P.R.C.

4box.it**4 BOX s.r.l.**

VAT IT07624080961

info@4box.it

phone +39 02 655 603 73

Registered office and operational headquarters

Via Filippo Brunelleschi, 16, 20166 Milan

Tax ID and Business Register No.:07624080961 - Economic and Administrative Index (R.E.A.) 1972154
Chamber of Commerce (C.C.I.A.A.) MI - Share Cap. € 20,000