



## TECHNICAL FEATURES

USB power supply 5 V, 3.0 A

U SERIES

5 V, 3.0 A USB power supply with one Type A and one Type C socket

### Application

For charging portable devices such as phones, smartphones, tablets, MP3 or MP4 players, speakers, watches, games consoles and powerbanks.

### USB compliance

LV directive, EMC directive, RoHS directive, ErP directive. Standards EN 62368-1:2014/A11:2017 Regulation (EU) 2019/1782.

### Installation

Do not install multiple adjacent power supplies. It is recommended to leave the module adjacent to the USB power supply free.

### Main features of USB power supplies

- USB power supply
- Input voltage: 100...240 V AC (50/60 Hz)
- Output voltage: 5 V, 3.0 A
- Overvoltage category (IEC 60364-4-44) CAT III
- Disconnection device with spacing between the contacts of at least 3 mm

### Material specifications

Base: PC / Cover: PC / UV-resistant

### Compatible with

Bticino®, Vimar®, Gewiss®.





### Recommended use

Circuit terminal output.


### Compatibility, codes and dimensions

Brand	Model	Colour	Code	A	B	C
Vimar®	Plana™	white	4B.V14.USB.30	44.80	47.40	22.30
	Arkè™	white	4B.V19B.USB.30	44.80	47.40	22.30
		grey	4B.V19.USB.30	44.80	47.40	22.30
		metal	4B.V19M.USB.30	44.80	47.40	22.30
Bticino®	Matix™	white	4B.AM.USB.30	43.35	47.20	23.24
	LivingLight™	white	4B.N.USB.30	43.90	47.20	21.80
		tech	4B.NT.USB.30	43.90	47.20	21.80
		anthracite	4B.L.USB.30	43.90	47.20	22.00
	LivingNow™	3 colours	4B.K.USB.30	85.20	47.20	44.10
	Axolute™	white	4B.HD.USB.30	45.23	47.20	22.23
		tech	4B.HC.USB.30	45.23	47.20	22.23
		anthracite	4B.HS.USB.30	45.23	47.20	22.23
Gewiss®	Chorus™	white	4B.G10.USB.30	47.20	44.00	22.23
		black	4B.G12.USB.30	47.20	44.00	22.23

Measurements in mm



### Connectors



CE Made in P.R.C.

4box.it