# 4b USB 2.1



## SPECIFICATION ITEMS

**USB Power supply 2.1 A - Type ouput A (5 V, 2.1 A)**

U SERIES

| Code | Image | Description |
|---|---|---|
| 4B.AM.USB |  | USB Power supply 2.1 A compatible with Bticino® Matix™;<br>100-230 V AC 50/60 Hz; 1 type output A, 5 V DC 2.1 A white |
| 4B.HD.USB |  | USB Power supply 2.1 A compatible with Bticino® Axolute™;<br>100-230 V AC 50/60 Hz; 1 type output A, 5 V DC 2.1 A white |
| 4B.L.USB |  | USB Power supply 2.1 A compatible with Bticino® Livinglight™ (Living International™);<br>100-230 V AC 50/60 Hz; 1 type output A, 5 V DC 2.1 A anthracite |
| 4B.N.USB |  | USB Power supply 2.1 A compatible with Bticino® Livinglight™ (Light™);<br>100-230 V AC 50/60 Hz; 1 type output A, 5 V DC 2.1 A white |
| 4B.NT.USB |  | USB Power supply 2.1 A compatible with Bticino® Livinglight™ (Light Tech™);<br>100-230 V AC 50/60 Hz; 1 type output A, 5 V DC 2.1 A tech |
| 4B.V14.USB |  | USB Power supply 2.1 A compatible with Vimat® Plana™;<br>100-230 V AC 50/60 Hz; 1 type output A, 5 V DC 2.1 A white |
| 4B.G12.USB |  | USB Power supply 2.1 A compatible with Gewiss® Chorus™;<br>100-230 V AC 50/60 Hz; 1 type output A, 5 V DC 2.1 A balck |

We reserve the right to modify prices, features, specifications, appearance, and availability of products and services without prior notice.
FINDER assumes no responsibility for any potential errors or insufficient information in this document. In the event of discrepancies between the printed and online versions, the latter shall prevail.
Finder S.p.A. and 4Box s.r.l. do not manufacture or market wall plates, mounting frames, or modular switches belonging to civil series of other companies. The trademarks mentioned belong to their respective owners.

December 2025 Rev.