4b USB 2.4



SPECIFICATION ITEMS

USB power supply 2.4 A - 2 type output A (5 V, 2.4 A)

U SERIES

Code	Image	Description
4B.AM.USB.24		USB power supply 2.4 A compatible with Bticino® Matix™; 100-230 V AC 50/60 Hz; 2 type output A, 5 V DC 2.4 A white
4B.G10.USB.24		USB power supply 2.4 A compatible with Gewiss® Chorus™; 100-230 V AC 50/60 Hz; 2 type output A, 5 V DC 2.4 A white
4B.L.USB.24		USB power supply 2.4 A compatible with Bticino® Livinglight™ (Living International™); 100-230 V AC 50/60 Hz; 2 type output A, 5 V DC 2.4 A anthracite
4B.N.USB.24		USB power supply 2.4 A compatible with Bticino® Livinglight™ (Light™); 100-230 V AC 50/60 Hz; 2 type output A, 5 V DC 2.4 A white
4B.NT.USB.24		USB power supply 2.4 A compatible with Bticino® Livinglight™ (Light Tech™); 100-230 V AC 50/60 Hz; 2 type output A, 5 V DC 2.4 A tech
4B.V14.USB.24		USB power supply 2.4 A compatible with Vimat® Plana™; 100-230 V AC 50/60 Hz; 2 type output A, 5 V DC 2.4 A white
4B.V19.USB.24		USB power supply 2.4 A compatible with Vimat® Arkè™; 100-230 V AC 50/60 Hz; 2 type output A, 5 V DC 2.4 A grey
4B.V19B.USB.24		USB power supply 2.4 A compatible with Vimat® Arkè™; 100-230 V AC 50/60 Hz; 2 type output A, 5 V DC 2.4 A white
4B.V19M.USB.24		USB power supply 2.4 A compatible with Vimat® Arkè™; 100-230 V AC 50/60 Hz; 2 type output A, 5 V DC 2.4 A metal

We reserve the right to modify prices, features, specifications, appearance, and availability of products and services without prior notice.
FINDER assumes no responsibility for any potential errors or insufficient information in this document. In the event of discrepancies between the printed and online versions, the latter shall prevail.
Finder S.p.A. and 4Box s.r.l. do not manufacture or market wall plates, mounting frames, or modular switches belonging to civil series of other companies. The trademarks mentioned belong to their respective owners.

December 2025 Rev.