



4b Externa IP40



TECHNICAL SPECIFICATIONS

2-module and 3-module IP40 enclosures

E SERIES

Applications

Applications include: Garages, cellars, balconies, terraces, porches, building perimeters, gardens, public bathrooms, changing rooms, industrial kitchens, and laboratories.

Conformance

RoHS II Directive 2011/65/EU + 2015/863/EU



Made in CN

IP40 enclosure with electrical socket

Plastic enclosure with IP40 protection rating with electrical sockets available in 2 or 3 modules

Compatible with the following residential and commercial wiring accessory systems:

Bticino®, Gewiss®

Main features

- IP40 protection rating
- 2-module or 3-module surface-mounted box
- Resistance to abnormal heat (Glow Wire Test): 650 °C
- Insulation resistance $>5M\Omega$ at 500 V DC
- Resistance to mechanical impacts: IK 08 (impacts up to 6J)
- Installation and operating temperature: -25 °C / +70 °C. Products compliant with the safety objectives of the L.V.
- Directive 2014/35/EU (Annex I)
- Resistant to water splashes and dust

Materials

Heat-resistant ABS-based technopolymer with high UV resistance, halogen-free.

Codes and dimensions

Type	Colour	Code	A	B	C
2-module	RAL 7035	4B.IP40.BT.CU	80.50	80.50	55.80
	RAL 7035	4B.IP40.H21	80.50	80.50	55.80
3-module	RAL 7035	4B.IP40.H21.CU	100.00	70.50	50.00
	RAL 7035	4B.IP40.H21.XL	100.00	70.50	50.00

Dimensions in mm

