



4b USB 2.1



TECHNICAL SPECIFICATIONS

USB Power supply 2.1 A - Type output A (5 V, 2.1 A)

U SERIES

Applications

Applications include the recharging of portable devices such as smartphones, tablets, MP3 or MP4 players, speakers, watches, game consoles and powerbanks.

Conformance

- Directives: LV Directive. EMC Directive. RoHS Directive. ErP Directive.
- Standards : EN IEC 62368-1, EN 55032, EN 55035, EN IEC 61000-3-2, EN 61000-3-3, EN 50563, EN IEC 63000.
- External power supplies regulation (EU) n. 2019/1782 REACH Regulation (EU) n. 1907/2006-art.33.

The product may contain traces of lead



Made in CN

Compatibility, codes and dimensions

Brand	System	Colour	Code	A	B	C
Vimar®	Plana™	white	4B.V14.USB	48.40	44.80	22.30
Bticino®	Matix™	white	4B.AM.USB	49.00	43.50	23.40
	Livinglight™	white (Light™)	4B.N.USB	47.00	44.10	21.80
		tech (Light Tech™)	4B.NT.USB	47.00	44.10	21.80
		anthracite (Living International™)	4B.L.USB	47.00	44.10	21.80
	Axolute™	white	4B.HD.USB			
Gewiss®	Chorus™	white	4B.G12.USB	48.20	46.00	22.00

Dimensions in mm

Main features

- USB power supply
- Input voltage: 100-230 V~ 50-60 Hz
- Output voltage: 5 V --- 2.1A
- Overvoltage category (EN 62109) Class III
- Disconnection device with a contact distance of at least 3 mm

Materials





Base: PC / Cover: PC / UV resistant

Installation guidelines

Do not install multiple power supplies side by side. It is recommended to leave the module adjacent to the USB power supply free. Install only one device per flush-mounting box.

Compatible with the following residential and commercial wiring accessory systems:

Bticino®, Vimar®, Gewiss®



Connector compatibility



USB A