



4b USB 3.0 CA



TECHNICAL SPECIFICATIONS

USB power supply 3 A - 2 type output C+A (5 V, 3 A)

U SERIES

USB Power Supply 5 V-3.0 A with one Type A and one Type C output.

Applications

Applications include the recharging of portable devices such as smartphones, tablets, MP3 or MP4 players, speakers, watches, game consoles and powerbanks.

Conformance

- Directives: LV Directive, EMC Directive, RoHS Directive, and ErP Directive.
- Standards: EN IEC 62368-1, EN 55032, EN 55035, EN IEC 61000-3-2, EN 61000-3-3, EN 50563, and EN IEC 63000.
- Regulations: External power supplies regulation (EU) n. 2019/1782 and REACH Regulation (EU) n. 1907/2006-art.33.

Note: The product may contain traces of lead.



Made in C.N.

Compatibility, codes and dimensions

Brand	System	Colour	Code	A	B	C
Bticino®	Axolute™	bianco	4B.HD.USB.30	45.20	47.00	22.40
		tech	4B.HC.USB.30	45.20	47.00	22.40
		antracite	4B.HS.USB.30	45.20	47.00	22.40
Gewiss®	Chorus™	bianco	4B.G10.USB.30	48.20	47.00	22.00
		nero	4B.G12.USB.30	48.20	47.00	22.00

Dimensions in mm

Connector compatibility



USB A



USB C

Main features

- USB power supply
- Input voltage: 100-230 V~ 50-60 Hz
- Output voltage: 5 V --- 3 A
- Overvoltage category (IEC 60364-4-44): CAT III
- Disconnection device with a contact distance of at least 3 mm

Materials

Base: PC / Cover: PC / UV resistant

Installation guidelines

Do not install multiple power supplies side by side. It is recommended to leave the module adjacent to the USB power supply free.

Recommended use

Circuit terminal output.

Compatible with the following residential and commercial wiring accessory systems:

Bticino®, Vimar®, Gewiss®

