4b USB CCA 20W

TECHNICAL SPECIFICATIONS
USB CCA 20 W power supply

USERIES

USB fast charge 20 W power supply with one Type A and one Type C output

Applications

Applications include the recharging of portable devices such as smartphones, tablets, MP3 or MP4 players, speakers, watches, game consoles and powerbanks.

Conformance

- Directives: LV Directive, EMC Directive, RoHS Directive, and ErP Directive.
- Standards: EN IEC 62368-1, EN 55032, EN 55035, EN IEC 61000-3-2, EN 61000-3-3, EN 50563, and EN IEC 63000.
- Regulations: External power supplies regulation (EU) n. 2019/1782 and REACH Regulation (EU) n. 1907/2006-art.33.

The product may contain traces of lead.

Made in CN

Materials

Base: PC / Cover: PC / UV resistant.

Main features

- USB A+C+C 20 W Power Delivery power supply
- Input voltage: 100-230 V~ 50-60 Hz
- Overvoltage category (IEC 60364-4-44): CAT III
- Device with a contact distance of at least 3 mm
- Electrical consumption: 420 mA a 100 V ~ /230 V ~
  - USB Type C: 5.0 ⎓ V DC 3.0 A; 9.0 V DC, 2.22 A; 12.0 V DC, 1.67 A (PD20W)
  - USB Type A: 5.0 V DC 3.0 A; 9.0 V DC, 2.2 A; 12.0 V DC, 1.67 A ⎓ (QC 20 W)
  - USB A+C : 5 V DC 3 A

Technical details

- Terminal type: screw
- Terminal capacity: 2 x 2.5 mm^2
- Stripping length: 7 mm
- Screwdriver: flat 3.5 mm
- Recommended use: circuit terminal output

Installation giudelines

Do not install multiple power supplies side by side.
It is recommended to leave the module adjacent to the USB power supply free.

Compatibility, codes and dimensions

Brand	System	Colour	Code	A	B	C
Vimar®	Linea™	3 colors	4BUSB20WCCA.V30	52.70	47.00	22.14
	Plana™	white	4BUSB20WCCA.V14	48.40	47.00	22.30
	Arkè™	white	4BUSB20WCCA.V19B	48.40	47.00	22.25
		grey	4BUSB20WCCA.V19	48.40	47.00	22.25
Bticino®	Matix™	white	4BUSB20WCCA.AM	48.50	47.00	23.24
	Livinglight™	white (Light™)	4BUSB20WCCA.N	47.00	47.00	21.80
		tech (Light Tech™)	4BUSB20WCCA.NT	47.00	47.00	21.80
		anthracite (Living International™)	4BUSB20WCCA.L	47.00	47.00	22.00
	LivingNow™	3 colors	4BUSB20WCCA.K	44.80	46.50	22.20

Dimensions in mm

Compatible with the following residential and commercial wiring accessory systems:

Bticino®, Vimar®.









Connector compatibility

USB A USB C

FINDER assumes no responsibility for any potential errors or insufficient information in this document. In case of discrepancies between the printed and online versions, the latter shall prevail. We reserve the right to make changes to prices, features, specifications, appearance, and availability of products and services without notice.